

Index For Synway's UC Series IP-PBXs

UC200..... 2

Key Features:

- 15~60 concurrent calls, 60~300 registered users
- Integrated 4 PSTN Trunk FXO Ports Plus 2 FXS Ports
- Comprehensive features for unified communications
- High level of security protection(SRTP, TLS & HTTPS)

UC500..... 4

Key Features:

- 30~100 Concurrent Calls, Dual Power Supply, 500+ Users
- IVR/Voice Mail/Fax/Conference/Recording/CDR/NAT Transverse
- High Level of Integrated Security Like SBC(SRTP, TLS & HTTPS)
- Interoperability With SIP/FXO/FXS (Integrated 2*FXS & 2*FXO)

UC500H..... 6

Key Features:

- 30~100 Concurrent Calls(Licensable to 100 Session), 1,000+ Users
- IVR/Voice Mail/Fax/Conference/Recording/CDR/NAT Transverse
- High Level of Integrated Security Like SBC(SRTP, TLS & HTTPS)
- Seamless Interoperability With SIP/E1/T1/FXO/FXS/Wireless

IP-PBX

- Up to 80 concurrent calls, 50-attendee conference
- Integrated 4 PSTN Trunk FXO Ports Plus 2 FXS Ports
- Comprehensive features for unified communication
- High level of security protection(SRTP, TLS & HTTPS)



The UC200 is an IP PBX appliance designed to bring enterprise-grade unified communications and security protection to all levels of businesses at an unprecedented price point without any licensing fees, costs-per-feature, or recurring fees. The UC200 enables enterprises to unify multiple communication technologies, such as comprehensive voice, fax, calling, conferencing, video/audio surveillance, data tools, security surveillance, mobility, and facility access management into one commonly managed or accessible network.

With a advanced hardware platform and software functionalities, the UC200 can support up to 500 registered users and offer effortless setup and deployment via the web-browser user interface. Besides auto-discovery of diverse endpoints and auto-provisioning, the UC200 series offers a set of comprehensive features, including customizable call-routing, multi-level IVRs, call queues, auto-attendant, call detail records (CDR), multi-site peering, voicemail/fax forwarding to email and more.

Key Features

- Supports up to 500 users, 50 SIP trunk accounts, up to 80 concurrent calls, 50 conference attendees
- Built-in call recording server; recordings accessed via web user interface
- Supports voicemail and fax forwarding to email
- Highest level of security protection using SRTP, TLS and HTTPS encryption
- Integrated 4 PSTN trunk FXO ports, 2 analog telephone FXS ports with lifeline capability
- Supports call queue for efficient call volume management
- Integrated LDAP and XML phonebooks, flexible dial plan
- Hi-speed network ports with Integrated NAT router and built-in firewall
- 1.5GHz ARM Quad-core processor, 1GB DDR RAM, 8GB EMMC Flash
- Supports up to a limitless-level IVR (Interactive Voice Response)
- Built-in Call Detail Records (CDR) for tracking phone usage by line, date, etc.
- Zero configuration provisioning of Mainstream SIP endpoints
- Multi-language auto-attendant to efficiently handle incoming calls



Hi-Interoperability with Network

UC200 has the super NAT network adaptability. In the system deployment, the remote SIP extension registered to the UC200 need not any NAT traversal setting.



Excellent Compatibility

Without NAT traversal setting, UC200 could be compliant with other mainstream SIP endpoints or components with changeable IP addresses, which effectively reduces complexity of configuration.



Flexible Resource Allocation

UC200 optimizes system resource utilization and system efficiency via stochastic algorithm, effectively minimizing hitting over processor resource and improving reliability in any scenarios.



High User-Friendliness

UC200 leverages autoclip intelligent inbound routing mechanism. With call records, UC 200 can intelligently match inbound call number with historic called one in autoclip. Moveable extension, call forwarding, DND, etc are available.



Multiple High-Security Modes

Multiple security mechanisms in UC200 are available, including password, ACL, data filtering, etc. Besides, outbound routing, DISA, conference, voice mail and other applications support PIN code setting to customize dynamic firewall.



Flexible Surveillance

UC200 adapts flexible multiple-layer monitoring modes to protect privacy at maximum level and ensure high-level of security and reliability in most conditions.

Technical Specifications

Interfaces	
Analog Telephone FXS Ports	2 ports (both with lifeline capability in case of power outage)
PSTN Line FXO Ports	4 ports (UC200)
Network Interfaces	Dual (UC200) 10/100 RJ45 ports
NAT Router	Yes (UC200)
Peripheral Ports	USB, TF
LED Indicators	Power/Ready, Network, PSTN Line, USB, TF
Reset Switch	Yes
Voice/Video Capabilities	
Voice-over-Packet Capabilities	LEC with NLP Packetized Voice Protocol Unit, 32~128ms-tail-length carrier grade Line Echo Cancellation, Dynamic Jitter Buffer
Voice and Fax Codecs	G.711 A-law/U-law, G.722, G.723.1 5.3K/6.3K, G.726, G.729A/B, GSM, AAL2-G.726-32; T.38
Video Codecs	H.264, H.263, H263+
QoS	Multiple Layers
Signaling & Control	
DTMF Methods	In Audio, RFC2833, and SIP INFO
Provisioning Protocol & Plug-and-Play	TFTP/HTTP/HTTPS, auto-discovery & auto-provisioning of various IP endpoints with no Configuration
Network Protocols	TCP/UDP/IP, RTP/RTCP, ICMP, ARP, DNS, DDNS, DHCP, NTP, TFTP, SSH, HTTP/HTTPS, PPPoE, SIP(RFC3261), STUN, SRTP, TLS, LADP
Disconnect Methods	Call Progress Tone, Polarity Reversal, Hook Flash Timing, Loop Current Disconnect, Busy Tone
Security	
Media Encryption	SRTP, TLS, HTTPS, TELNET with Fail2ban, Whitelist, Blacklist, alerts and more to protect against attacks
Physical	
Power Supply	Output: 12VDC, 2A; Input: 100 ~ 240VAC, 50 ~ 60Hz
Dimensions	UC200: 186mm L x 108mm W x 30mm H
Weight	UC200: Unit weight 0.83kg, Package weight 1.1kg
Environmental	Operating: 32 ~ 113°F / 0 ~ 45°C, 8 ~ 90% (non-condensing); Storage: -4 ~ 185°F / -20 ~ 85°C
Mounting	Desktop
Additional Features	
Multi-Language Support	English/Chinese/Traditional Chinese for Web UI; Customizable IVR/voice prompts for English, Chinese, British English; Customizable language pack to support any other languages
Caller ID	Bellcore/Telcordia, ETSI-FSK, ETSI-DTMF
Polarity Reversal/Wink	Yes, with enable/disable option upon call establishment and termination
Call Center	Multiple configurable call queues, automatic call distribution (ACD) based on agent skills/availability/ busy level, in-queue announcement
Customizable Auto Attendant	Unlimited layers of IVR (Interactive Voice Response)
Maximum Call Capacity	Up to 50 even in SRTP encrypted
Conference Bridges	Up to 25 simultaneous PSTN or IP participants
Call Features	Call park, call forward, call transfer, DND, ring/hunt group, paging/intercom etc.

IP-PBX

- 20/40/60/80/100 concurrent calls, 80-attendee conference
- Dual Power Supply to Protect Your System
- Comprehensive features for unified communication
- High level of security protection(SRTP, TLS & HTTPS)



The UC500 is an IP PBX appliance designed to bring enterprise-grade unified communications and security protection to all levels of businesses at an unprecedented price point without any licensing fees, costs-per-feature, or recurring fees. The UC500 enables enterprises to unify multiple communication technologies, such as comprehensive voice, fax, calling, conferencing, video/audio surveillance, data tools, security surveillance, mobility, and facility access management into one commonly managed or accessible network.

With a advanced hardware platform and software functionalities, the UC500 can support up to 500 registered users and offer effortless setup and deployment via the web-browser user interface. Besides auto-discovery of diverse endpoints and auto-provisioning, the UC500 series offers a set of comprehensive features, including customizable call-routing, multi-level IVRs, call queues, auto-attendant, call detail records (CDR), multi-site peering, voicemail/fax forwarding to email and more.

Key Features

- Supports up to 500 users, up to 100 concurrent calls, 80 conference attendees
- Built-in call recording server; recordings accessed via web user interface
- Supports voicemail and fax forwarding to email
- Highest level of security protection using SRTP, TLS and HTTPS encryption
- Integrated 4 PSTN trunk FXO ports, 2 analog telephone FXS ports with lifeline capability
- Supports call queue for efficient call volume management
- Integrated LDAP and XML phonebooks, flexible dial plan
- Hi-speed network ports with Integrated NAT router and built-in firewall
- 1.5GHz ARM Quad-core processor, 2GB DDR RAM, 16GB EMMC Flash
- Supports up to a limitless-level IVR (Interactive Voice Response)
- Built-in Call Detail Records (CDR) for tracking phone usage by line, date, etc.
- Zero configuration provisioning of Mainstream SIP endpoints
- Multi-language auto-attendant to efficiently handle incoming calls



Hi-Interoperability with Network

UC500 has the super NAT network adaptability. In the system deployment, the remote SIP extension registered to the UC500 need not any NAT traversal setting.



Excellent Compatibility

Without NAT traversal setting, UC500 could be compliant with other mainstream SIP endpoints or components with changeable IP addresses, which effectively reduces complexity of configuration.



Flexible Resource Allocation

UC500 optimizes system resource utilization and system efficiency via stochastic algorithm, effectively minimizing hitting over processor resource and improving reliability in any scenarios.



High User-Friendliness

UC500 leverages autclip intelligent inbound routing mechanism. With call records, UC500 can intelligently match inbound call number with historic called one in autclip. Moveable extension, call forwarding, DND, etc are available.



Multiple High-Security Modes

Multiple security mechanisms in UC500 are available, including password, ACL, data filtering, etc. Besides, outbound routing, DISA, conference, voice mail and other applications support PIN code setting to customize dynamic firewall.



Flexible Surveillance

UC500 adapts flexible multiple-layer monitoring modes to protect privacy at maximum level and ensure high-level of security and reliability in most conditions.

Technical Specifications

Interfaces

Analog Telephone FXS Ports	2 ports (both with lifeline capability in case of power outage)
PSTN Line FXO Ports	2 ports (UC500)
Network Interfaces	Dual (UC500) 10/100 RJ45 ports
NAT Router	Yes (UC500)
Peripheral Ports	USB, TF
LED Indicators	Power/Ready, Network, PSTN Line, USB, TF
Reset Switch	Yes

Voice/Video Capabilities

Voice-over-Packet Capabilities	LEC with NLP Packetized Voice Protocol Unit, 32~128ms-tail-length carrier grade Line Echo Cancellation, Dynamic Jitter Buffer
Voice and Fax Codecs	G.711 A-law/U-law, G.722, G.723.1 5.3K/6.3K, G.726, G.729A/B, GSM, AAL2-G.726-32; T.38
Video Codecs	H.264, H.263, H263+
QoS	Multiple Layers

Signaling & Control

DTMF Methods	In Audio, RFC2833, and SIP INFO
Provisioning Protocol & Plug-and-Play	TFTP/HTTP/HTTPS, auto-discovery & auto-provisioning of various IP endpoints with no Configuration
Network Protocols	TCP/UDP/IP, RTP/RTCP, ICMP, ARP, DNS, DDNS, DHCP, NTP, TFTP, SSH, HTTP/HTTPS, PPPoE, SIP(RFC3261), STUN, SRTP, TLS, LADP
Disconnect Methods	Call Progress Tone, Polarity Reversal, Hook Flash Timing, Loop Current Disconnect, Busy Tone

Security

Media Encryption	SRTP, TLS, HTTPS, TELNET with Fail2ban, Whitelist, Blacklist, alerts and more to protect against attacks
------------------	----------------------------------------------------------------------------------------------------------

Physical

Power Supply	Input: 100 ~ 220VAC
Dimensions	UC500: 440mm L x 202mm W x 44mm H
Weight	UC500: Unit weight 2.52kg
Environmental	Operating: 32 ~ 113°F / 0 ~ 45°C, 8 ~ 90% (non-condensing); Storage: -4 ~ 185°F / -20 ~ 85°C
Mounting	Desktop

Additional Features

Multi-Language Support	English/Chinese/Traditional Chinese for Web UI; Customizable IVR/voice prompts for English, Chinese, British English; Customizable language pack to support any other languages
Caller ID	Bellcore/Telcordia, ETSI-FSK, ETSI-DTMF
Polarity Reversal/Wink	Yes, with enable/disable option upon call establishment and termination
Call Center	Multiple configurable call queues, automatic call distribution (ACD) based on agent skills/availability/ busy level, in-queue announcement
Customizable Auto Attendant	Unlimited layers of IVR (Interactive Voice Response)
Maximum Call Capacity	Up to 50 even in SRTP encrypted

IP-PBX

- 20~100 Concurrent Calls, 1,000 Users, 50-Attendee Conference
- UC Features:IVR/Voice Mail/Fax/Recording/CDR/NAT Transverse
- High Level of Integrated Security Like SBC(SRTP, TLS & HTTPS)
- Seamless Interoperability With PSTN: E1/T1/FXO/FXS/Wireless
- Built-in Server (Optional) to Run Any Third-Party Applications



The UC500H is a Hybrid IP-PBX appliance designed to bring enterprise-grade unified communications and security protection to all levels of businesses at an unparalleled price point without any licensing fees, costs-per-feature, or recurring fees. The UC500H enables enterprises to unify multiple communication technologies in hybrid PSTN and VoIP networks, such as comprehensive voice, fax, calling, conferencing, video/audio surveillance, data tools, security surveillance, mobility, and facility access management into one commonly managed or accessible network.

With an advanced hardware platform, dual power supply and software functionalities, the UC500H can support up to 1,000 registered users and offer effortless setup and deployment via the web-browser user interface. Besides auto-discovery of diverse endpoints and auto-provisioning, the UC500H series offers a set of comprehensive features, including customizable call-routing, multi-level IVRs, call queues, auto-attendant, call detail records (CDR), multi-site peering, voicemail/fax forwarding to email and more.

Key Features

- Supports up to 1000 users, 100 SIP trunk accounts, up to 100 concurrent calls, 50 conference attendees
- Integrated modular design: interface with T1/E1/FXO/FXS/GSM/WCDMA/VoLTE
- Supports up to a limitless-level IVR (Interactive Voice Response)
- Built-in call recording server; recordings accessed via web user interface
- Supports call queue for efficient call volume management
- Built-in Call Detail Records (CDR) for tracking phone usage by line, date, etc.
- Supports voicemail and fax forwarding to email
- Integrated LDAP and XML phonebooks, flexible dial plan
- Zero configuration provisioning of Mainstream SIP endpoints
- Highest level of security protection using SRTP, TLS and HTTPS encryption
- Hi-speed network ports with Integrated NAT router and built-in firewall
- Multi-language auto-attendant to efficiently handle incoming calls
- 1.5GHz ARM Quad-core processor, 2GB DDR RAM, 16GB EMMC Flash
- Optional industrial servers to run any add-on third-party applications



Hi-Interoperability with Network

UC500H has the super NAT network adaptability. In the system deployment, the remote SIP extension registered to the UC500H need not any NAT traversal setting.



Excellent Compatibility

Without NAT traversal setting, UC500H could be compliant with other mainstream SIP endpoints or components with changeable IP addresses, which effectively reduces complexity of configuration.



Intelligent Resource Allocation

UC500H optimizes system resource utilization and system efficiency via stochastic algorithm, effectively minimizing hitting over processor resource and improving reliability in any scenarios.



High User-Friendliness

UC500H leverages autoclip intelligent inbound routing mechanism. With call records, UC 500H can intelligently match inbound call number with historic called one in autoclip. Moveable extension, call forwarding, DND, etc are available.



Multiple High-Security Modes

Multiple security mechanisms in UC500H are available, including password, ACL, data filtering, etc. Besides, outbound routing, DISA, conference, voice mail and other applications support PIN code setting to customize dynamic firewall.



Flexible Surveillance

UC500H adapts flexible multiple-layer monitoring modes to protect privacy at maximum level and ensure high-level of security and reliability in most conditions.

Technical Specifications

Interfaces

Analog Telephone FXS Ports	16 ports (both with lifeline capability in case of power outage)
PSTN Line FXO Ports	16 ports (UC500H)
Wireless Ports	8 ports (GSM/WCDMA/VoLTE)
Digital Trunking	1/2/4E1/T1 (PRI ISDN/SS7)
Network Interfaces	Dual (UC500H) 100/1000M RJ45 ports
NAT Router	Yes (UC500H)
Peripheral Ports	USB, TF
LED Indicators	Power/Ready, Network, PSTN Line, USB, TF
Reset Switch	Yes

Voice/Video Capabilities

Voice-over-Packet Capabilities	LEC with NLP Packetized Voice Protocol Unit, 32~128ms-tail-length carrier grade Line Echo Cancellation, Dynamic Jitter Buffer
Voice and Fax Codecs	G.711 A-law/U-law, G.722, G.723.1 5.3K/6.3K, G.726, G.729A/B, GSM, AAL2-G.726-32; T.38
Video Codecs	H.264, H.263, H263+
QoS	Multiple Layers

Signaling & Control

DTMF Methods	In Audio, RFC2833, and SIP INFO
Provisioning Protocol & Plug-and-Play	TFTP/HTTP/HTTPS, auto-discovery & auto-provisioning of various IP endpoints with no Configuration
Network Protocols	TCP/UDP/IP, RTP/RTCP, ICMP, ARP, DNS, DDNS, DHCP, NTP, TFTP, SSH, HTTP/HTTPS, PPPoE, SIP(RFC3261), STUN, SRTP, TLS, LADP
Disconnect Methods	Call Progress Tone, Polarity Reversal, Hook Flash Timing, Loop Current Disconnect, Busy Tone

Security

Media Encryption	SRTP, TLS, HTTPS, TELNET with Fail2ban, Whitelist, Blacklist, alerts and more to protect against attacks
------------------	----------------------------------------------------------------------------------------------------------

Physical

Power Supply	Output: 12VDC, 2A; Input: 100 ~ 240VAC, 50 ~ 60Hz
Dimensions	UC500H: 430mm L x 483mm W x 88mm H
Weight	UC500H: About 8.8Kg (Weight varies with diverse internal TDM modules)
Environmental	Operating: 32 ~ 113°F / 0 ~ 45°C, 8 ~ 90% (non-condensing); Storage: -4 ~ 185°F / -20 ~ 85°C
Mounting	Desktop

Additional Features

Multi-Language Support	English/Chinese/Traditional Chinese for Web UI; Customizable IVR/voice prompts for English, Chinese, British English; Customizable language pack to support any other languages
Caller ID	Bellcore/Telcordia, ETSI-FSK, ETSI-DTMF
Polarity Reversal/Wink	Yes, with enable/disable option upon call establishment and termination
Call Center	Multiple configurable call queues, automatic call distribution (ACD) based on agent skills/availability/ busy level, in-queue announcement
Customizable Auto Attendant	Unlimited layers of IVR (Interactive Voice Response)
Maximum Call Capacity	Up to 100 even in SRTP encrypted
Conference Bridges	Up to 50 simultaneous PSTN or IP participants
Call Features	Call park, call forward, call transfer, DND, ring/hunt group, paging/intercom etc.



Since
1992



CTI and
Vo P Gateway



1000+
employees



3000+
Partners

As a leading VoIP enabling-technologies provider in China, Synway has been partnered with applications & solution providers worldwide to deliver turkey solutions for enterprises and telecom carriers. Based on long-standing business network, Synway's appliances and equipments, with third-party compliant software platforms from mainstream application providers, have served 5,000 plus customers, including contact centers, financial institutes, public security, government agencies, service providers, hospitality and operators.

In ever-changeable environments, Synway's long-term goal would be of partnership with vendors of cloud-based unified communications, providing enterprises and SPs with a complete range of cloud-based applications, including Video and Audio Conferencing, Contact Center, IP-PBX, Unified Messaging, Social Media Services and more. For in-house IPR and better customer value, Synway provides strategic partners with customized OEM or ODM services to localize more efficiently. To achieve 0-defective rate, Synway has adopted ISO9001, CE, FCC, RoHS, 3C and more since 2001.

Synway Information Engineering Co., Ltd. (Headquarter)
Synway R&D Building, No.3756, Rd. Nanhuan.
Binjiang District, Hangzhou, P.R.China 310053
Tel: (86) 571 88860561
Fax: (86) 571 88850923
Email: info@synway.net
All Copyrights are reserved. Jan 2018

Technical Support
Tel: (86) 571 86692545
Tel: (86) 571 88864579
Mobile: (86) 18905817070 (24*7)
Email:techsupport@synway.net

No notice for any change in future in this catalog, For more information or latest update, please visit Synway website.