

DTP800

series E1/T1 Call Recording Server

Call recording, as a basic function of communication system, has its tangible value and been widely used. At present, Synway has the world's most complete production range, including: Analog passive recording, E1/T1 passive recording, digital phoneset passive recording, VoIP recording and others.

In order to adapt to the global demand for diverse market segments, Synway recently released DTP800 series, which combines over 20 years expertise in the recording field with accumulated hardware and software development experience. It is mainly applicable to passively tap and monitor E1/T1 lines in PSTN environment. The system is highly stable and reliable, and users can query, play out and monitor the device through network settings. Other main features include data backup in diverse servers, account management, the Web browsing and administration over the recording file and so on.



Key Features and Benefits

- **1U height, standard rack design**
- **support bidirectional recording for 1~8E1/T1 interface**
- **support the global protocols with high interoperability**
- **support DSP-based compression coding format**
- **web-based recording system management software**
- **support recording data storage, query and real-time monitoring**

- **Support multiple protocols and recording modes**

DTP800 supports 8 E1/T1 ports at maximum, a range of protocols such as SS1, SS7 (Tup, ISUP), ISDN signaling call status analysis and voice signal analysis, and can be configured for inbound recording, outbound recording, and mixed in/outbound ones.

- **Support multiple speech coding formats**

DTP800 supports DSP-based a-law (g. 711), M-law, IMA-ADPCM, GSM, MP3 and G. 729A format coding, and software processing -linear PCM, VOX format Codecs. It can adapt to any recording environment in the world for short time to market.

- **Adopt hi-impedance multiplexing mode**

DTP800 supports high impedance, and does not affect the normal operation of the system. And DTP800 has a strong signal adaptive ability, and can tap into line at any point to monitor call conversation.

DTP800 series E1/T1 Call Recording Server Gateway



- [Have recording data storage, query function](#)

DTP800 supports recording data storage, query function, exporting data report. With 2T data hard disk, it can work in uninterrupted 96 days. Recording data can also be stored offsite over the network.

Technical Specifications:

- [Configuration](#)

DTP800-1 E1/T1: Intel 1.8G Dual core CPU,1T HDD

DTP800-2 E1/T1: Intel 1.8G Dual core CPU,1T HDD

DTP800-4 E1/T1: Intel 1.8G Dual core CPU,2T HDD

DTP800-8E1/T1: Intel 1.8G Dual core CPU,2T HDD

- [Dimensions](#)

440×44×200 mm(long*High*Deep)

- [Weight:](#)

About 3 kg (Excluding hard disk and accessories)

- [Environment](#)

Operating temperature: 0°C —55°C

Storage temperature: -20°C —85°C

Humidity: 8%— 90% non-condensing

Storage humidity: 8%— 90% non-condensing

- [Input/output Interface](#)

E1 Physical Ports: compliant with G703, including 75Ω unbalanced interface and 120Ω balanced interface

T1 Physical Ports DSX-1 and CSU line build-outs available for different extents of signal losses, including 100Ω and 110Ω balanced interfaces

- [Signaling:](#)

SS1: compliant with international GF002-9002 (DL and MFC)

SS7: compliant with Q771-Q795

DSS1: compliant with Q.933

ISDN-PRI

- [Audio Specifications](#)

Codec: CCITT A/μ-Law 64kbps

IMA ADPCM 32kbps

G.729A 8kbps

GSM 13.6kbps

MP3 8/16kbps

Frequency response: 300-3400Hz(±3dB)

AGC:-20db—0db

- [Maximum System Capacity](#)

Up to 8E1/T1 in single chassis

- [Power Requirements](#)

Maximum power consumption: ≤28W

Input impedance: 1 KΩ(AC)

Input interface: RJ48C

- [Audio Encoding & Decoding](#)

16Bit PCM 128kbps

ADPCM 32kbps

8Bit PCM 64kbps

GSM 13.6kbps

A-Law 64kbps

MP3 8/16kbps

μ-Law 64kbps

G.729A 8kbps

VOX 32kbps

- [Sampling Rate](#)

8kHz

- [Safety](#)

Lightning resistance: Level 4

- [Certification](#)

International standards

About Synway

As a major manufacturer and supplier of communication products and solutions, Synway specializes in providing superior Multimedia Gateway, Integrated Multimedia Switch, Telephony Hardware in use for Telecom communications. www.synway.net

Synway Information Engineering Co., Ltd.

Synway R&D Building, No.3756, Rd. Nanhuan, Binjiang District, Hangzhou, P.R.China 310053

Tel: (86) 571 88860561; Fax: (86) 571 88850923; Email: info@synway.net

Copyright © Synway. All rights reserved.